

Page: 1 of 6

This version issued September, 2016

Emergency Contact: 13 11 26 (Australia wide)

Section 1 - Identification of the Material and Supplier

E.D. Oates Pty Ltd Trading as Research Products

13-21 Maygar Boulevard Broadmeadows, Vic, 3047

Phone: 1300 669 686 (business hours)

Fax: (03) 9359 9509

Email: customerservice@oates.com.au Website: www.oateslaboratories.com.au

Chemical nature: Water solution of potassium hydroxide and other ingredients.

Trade Name: PUNCH

Product Use: Cleaner for ceramic tiles, guarry pavers and concrete floors.

Creation Date: August, 2013

This version issued: Septemebr, 2016 and is valid for 5 years from this date.

Section 2 - Hazards Identification

GHS Pictogram

GHS05: Corrosion.

GHS07: Exclamation mark. GHS09: Environment.



GHS Signal word: DANGER

HAZARD CLASSIFICATION

Skin corrosion.

Serious eye damage.

HAZARD STATEMENT:

H290: Corrosive to metals. H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H402: Harmful to aquatic life.

PREVENTION

P102: Keep out of reach of children.

P260: Do not breathe fumes, mists, vapours or spray.

P264: Wash contacted areas thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P280: Wear protective gloves, protective clothing and eye or face protection.

RESPONSE

P310: Immediately call a POISON CENTRE or doctor/physician.

P330: Rinse mouth.

P363: Wash contaminated clothing before reuse.

P301+P312: IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

P303+P361+P351: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse cautiously with water for several minutes.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313: If skin irritation occurs: Get medical advice. P337+P313: If eye irritation persists: Get medical advice.

P391: Collect spillage.

P370+P378: Not combustible. Use extinguishing media suited to burning materials. Water fog or fine spray is the preferred medium for large fires.

SAFETY DATA SHEET

Poisons Information Centre: 13 11 26 from anywhere in Australia, (0800 764 766 in New Zealand)



E.D. Oates Pty Ltd

ABN 61 004 329 462

13-21 Maygar Boulevard, Broadmeadows Vic 3047 Customer Service: 1300 669 686 | Website: www.oateslaboratories.com.au



Page: 2 of 6

This version issued September, 2016

Emergency Contact: 13 11 26 (Australia wide)

STORAGE

P402+P404: Store in a dry place. Store in a closed container. P403+P235: Store in a well-ventilated place. Keep cool.

DISPOSAL

P501: Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

Emergency Overview

Physical Description & Colour: Colourless to light yellow coloured liquid.

Odour: Mild, slightly sweet odour.

Major Health Hazards: Harmful if swallowed. Causes severe skin burns and eye damage. Corrosive to metals.

SUSMP Classification: S6 (POISON)

Potential Health Effects

Inhalation:

Short Term Exposure: Available data indicates that this product is not harmful. In addition product is unlikely to cause any discomfort or irritation.

Long Term Exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short Term Exposure: Available data indicates that this product is very corrosive to the skin. Capable of causing severe burns with deep ulceration, and can penetrate to deeper layers of skin resulting in third degree burns. Corrosion will continue until product is removed or neutralised. Severity depends on concentration and duration of exposure. Burns may not be immediately painful; the onset of pain may be minutes to hours.

Long Term Exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short Term Exposure: This product is very corrosive to eyes. It will quickly cause severe pain, and corrosion of the eye and surrounding facial tissues. Unless exposure is immediately treated, permanent blindness and facial scarring will occur.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. Available data shows that this product is harmful, but symptoms are not available. However, this product is very corrosive to the gastrointestinal tract. Capable of causing severe burns with deep ulceration, and can penetrate to deeper layers of skin resulting in third degree burns. Corrosion will continue until product is removed or neutralised. Severity depends on concentration and duration of exposure.

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA. **NTP:** No significant ingredient is classified as carcinogenic by NTP. **IARC:** No significant ingredient is classified as carcinogenic by IARC.

Section 3 – Composition/Information on Ingredients

Ingredients	CAS No	Conc., %	TWA (mg/m³)	STEL (mg/m³)
Potassium hydroxide	1310-58-3	10-30	2	Peak
Sodium metasilicate	6834-92-0	<10	not set	not set
Alkyl polyglucoside	68515-73-1	<5	not set	not set
Other non hazardous ingredients	secret	10-30	not set	not set
Water	7732-18-5	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

SAFETY DATA SHEET

Poisons Information Centre: 13 11 26 from anywhere in Australia, (0800 764 766 in New Zealand)



E.D. Oates Pty Ltd

13-21 Maygar Boulevard, Broadmeadows Vic 3047

Customer Service: 1300 669 686 | Website: www.oateslaboratories.com.au

ABN 61 004 329 462



Page: 3 of 6

This version issued September, 2016

Emergency Contact: 13 11 26 (Australia wide)

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 11 26 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. **Skin Contact:** Seek urgent medical attention. Flush contaminated area with lukewarm, gently flowing water for at least 60 minutes, by the clock. DO NOT INTERRUPT FLUSHING. If necessary, keep emergency vehicle waiting (show paramedics this SDS and take their advice). Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Strongly basic ingredients tend to penetrate the skin and so need longer rinsing than other substances.

Eye Contact: Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 60 minutes, by the clock, while holding the eyelid(s) open. Neutral saline solution may be used as soon as it is available. DO NOT INTERRUPT FLUSHING. If necessary, keep emergency vehicle waiting (show paramedics this MSDS and take their advice). Take care not to rinse contaminated water into the unaffected eye or onto face. Call a Poisons Information Centre or a doctor urgently. Take special care if exposed person is wearing contact lenses.

Ingestion: If swallowed, do NOT induce vomiting; rinse mouth thoroughly with water and contact a Poisons Information Centre. Urgent hospital treatment is likely to be needed. Give activated charcoal if instructed.

Section 5 – Fire Fighting Measures

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is little risk of an explosion from this product if commercial quantities are involved in a fire.

This product is likely to decompose only after heating to dryness, followed by further strong heating.

Extinguishing Media: Not combustible. Use extinguishing media suited to burning materials. Water fog or fine spray is the preferred medium for large fires. Aim to dilute the material with large quantities of water. If practical, contain diluted material and prevent from entering drains and water courses.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. There is little danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is liquid-tight chemical protective clothing and breathing apparatus.

Flash point: Does not burn.

Upper Flammability Limit: Does not burn.

Lower Flammability Limit: Does not burn.

Autoignition temperature: Not applicable - does not burn.

Flammability Class: Does not burn.

Section 6 - Accidental Release Measures

Accidental release: This product is sold in small packages, and the accidental release from one of these is not usually a cause for concern. For minor spills, clean up, rinsing to sewer and put empty container in garbage. Although no special protective clothing is normally necessary because of occasional minor contact with this product, it is good practice to wear impermeable gloves when handling chemical products. In the event of a major spill, prevent spillage from entering drains or water courses and call emergency services.

Section 7 – Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

SAFETY DATA SHEET

Poisons Information Centre: 13 11 26 from anywhere in Australia, (0800 764 766 in New Zealand)





Page: 4 of 6

This version issued September, 2016

Emergency Contact: 13 11 26 (Australia wide)

Storage: This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Store in a cool, well ventilated area. Check containers periodically for corrosion and leaks. Containers should be kept closed in order to minimise contamination. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 2500kg or L of Dangerous Goods of Packaging Group II, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

Section 8 – Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits TWA (mg/m³) STEL (mg/m³)

Potassium hydroxide 2 Peak

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems. **Ventilation:** This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a

fan is suggested. **Eye Protection:** Your eyes must be completely protected from this product by splash resistant goggles with face shield. All surrounding skin areas must be covered. Emergency eye wash facilities must also be available in an area close to where this product is being used.

Skin Protection: Because of the dangerous nature of this product, make sure that all skin areas are completely covered by impermeable gloves, overalls, hair covering, apron and face shield. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: rubber, Viton, nitrile, butyl rubber, Barricade, neoprene, Teflon, polyethylene, PE/EVAL, Saranex, Responder.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

Section 9 - Physical and Chemical Properties

Physical Description & colour: Light brown coloured liquid.

Odour: Mild, slightly sweet odour.

Approximately 100°C at 100kPa.

Freezing/Melting Point: Below 0°C.

Volatiles: Water component.

Vapour Pressure: 2.37 kPa at 20°C (water vapour pressure).

Vapour Density: As for water.

Specific Gravity: 1.20

Water Solubility: Completely soluble in water.

pH: 13.00-14.00
Volatility: No data.
Odour Threshold: No data.
Evaporation Rate: As for water.
Coeff Oil/water Distribution: No data

Autoignition temp: Not applicable - does not burn.

Section 10 – Stability and Reactivity

Reactivity: Most strong alkalis and bases react with inorganic and organic acids to form salts. They can also react with some metals liberating hydrogen gas. These reactions may be rapid and sometimes liberate much heat. They can also decompose many organic materials such as esters, in a reaction called hydrolysis.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Containers should be kept dry. Handle and open containers carefully.

SAFETY DATA SHEET

Poisons Information Centre: 13 11 26 from anywhere in Australia, (0800 764 766 in New Zealand)

E.D. Oates Pty Ltd

13-21 Maygar Boule

ABN 61 004 329 462

13-21 Maygar Boulevard, Broadmeadows Vic 3047

Customer Service: 1300 669 686 | Website: www.oateslaboratories.com.au



Page: 5 of 6

This version issued September, 2016

Emergency Contact: 13 11 26 (Australia wide)

Incompatibilities: acids, zinc, tin, aluminium and their alloys, other materials reactive with extremely alkaline liquids.

Fire Decomposition: This product is likely to decompose only after heating to dryness, followed by further strong heating. Potassium, silicon and sodium compounds.

Polymerisation: This product will not undergo polymerisation reactions.

Section 11 – Toxicological Information

Local Effects:

Target Organs: There is no data to hand indicating any particular target organs.

Classification of Hazardous Ingredients

Ingredient Hazard Statements

Potassium hydroxide H302: Harmful is swallowed.

H314: Causes severe skin burns and eye damage.

Sodium metasilicate H290: May be corrosive to metals.

H314: Causes severe skin burns and eye damage.

H335: May cause respiratory irritation. H318: Causes serious eye damage.

Health Effects - Acute

Alkyl polyglucoside

Swallowed: May be irritating to digestive system if swallowed.

Eye: Causes serious eye damage.

Skin: Causes severe skin burns and eye damage.

Inhaled: May cause respiratory irritation.

Section 12 - Ecological Information

This product is harmful to aquatic organisms. Insufficient data to be sure of status. However, until diluted or neutralised it will kill all aquatic organisms it contacts due to extreme pH.

Section 13 - Disposal Considerations

Disposal: Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

Section 14 – Transport Information

ADG Code: 1719, CAUSTIC ALKALI LIQUID, N.O.S.

Hazchem Code: 2RE Special Provisions: 274

Limited quantities: ADG 7 specifies a Limited Quantity value of 1 L for this class of product.

Dangerous Goods Class: Class 8: Corrosive Substances.

Packaging Group: II

Packaging Method: P001, IBC02

Class 8 Corrosive Substances shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances where the Toxic Substances are cyanides and the Corrosives are acids), 7 (Radioactive Substances), Foodstuffs and foodstuff empties. They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases), 2.2 (Non-Flammable, Non-Toxic Gases), 2.3 (Poisonous Gases), 3 (Flammable liquids), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 6 (Toxic Substances except where the Toxic Substances are cyanides and the Corrosives are acids) and 9 (Miscellaneous Dangerous Goods).

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

SAFETY DATA SHEET

Poisons Information Centre: 13 11 26 from anywhere in Australia, (0800 764 766 in New Zealand)



E.D. Oates Pty Ltd ABN 61 004 329 462

13-21 Maygar Boulevard, Broadmeadows Vic 3047

Customer Service: 1300 669 686 | Website: www.oateslaboratories.com.au



Page: 6 of 6

This version issued September, 2016

Emergency Contact: 13 11 26 (Australia wide)

The following ingredients: Potassium hydroxide, Sodium metasilicate (an alkaline salt), are mentioned in the SUSMP.

Section 16 – Other Information

This SDS contains only safety-related information. For other data see product literature.

Emergency Contact: Phone 13 11 26 (Australia wide)

Acronyms:

ADG Code Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition)

AUCS
SWA
Australian Inventory of Chemical Substances
Safe Work Australia, formerly ASCC and NOHSC
CAS number
Chemical Abstracts Service Registry Number

Hazchem Code Emergency action code of numbers and letters that provide information to emergency

services especially firefighters

IARC International Agency for Research on Cancer

NOS Not otherwise specified

NTP National Toxicology Program (USA)

R-Phrase Risk Phrase

SUSMP Standard for the Uniform Scheduling of Medicines & Poisons

UN Number United Nations Number

Please read all labels carefully before using product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

This SDS is prepared in accord with the SWA document "Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals" (February 2016).

End of Safety Data Sheet



Poisons Information Centre: 13 11 26 from anywhere in Australia, (0800 764 766 in New Zealand)



ABN 61 004 329 462